

INSULATED TRAFFIC DOOR SPECIFICATIONS



MAXIMUM DOOR SIZE:

- Up to 2750mm High x 2400mm Wide.

DOOR PANEL SPECIFICATIONS:

- Constructed from a custom rigid P.V.C. extrusion with thermo-plastic facings and insulated core
- Side mounted top hinge system and floor mounted bottom hinge.
- Outer skin ABS plastic.
- Thickness: 42mm.
- Colours: dark grey, light grey, beige and black.
- Internal sub frame manufactured from P.V.C. filled with P.I.R. foam.
- Supplied with full perimeter gasket around door frame, manufactured from a semi-rigid rubber strip.
- Window Sizes: 740mm High x 235mm Wide 540mm High x 540mm Wide
- Bumper Panels: Spring bumpers or flat panels are available to cushion the impact from motorised or hand traffic vehicles.



call free: 0800 267 888 e: info@flexibledoors.co.nz www.flexibledoors.co.nz Postal: PO Box 7487 Christchurch, 8240

CHRISTCHURCH: 9 Lock Crescent, Hillsborough, Christchurch 8022, New Zealand.
 AUCKLAND: 43A Hobill Avenue, Wiri, Auckland 2104, New Zealand.

p: +64 3 384 8036, f: +64 3 384 8046
p: +64 9 580 2440, f: +64 9 580 2442